



Application Tape

Premasking and Prespacing Tapes

Product Bulletin

Products This Bulletin provides an overview of all 3M premasking and prespacing tape. All product-specific information is included in this bulletin.

Product Line	premasking	3M™ Premasking Tape SCPM-19 3M™ Premasking Tape SCPM-44X
	prespacing	3M™ Prespacing Tape SCPS-2 3M™ Prespacing Tape SCPS-55 3M™ Prespacing Tape SCPS-100 3M™ Prespacing Tape IAT ecg

Product Characteristics These are typical values for unprocessed products. Contact your 3M representative for a custom specification.

Physical & Application	Material	paper
	Thickness (paper)	110 µm to 120 µm (0.11 mm to 0.12 mm)
	Adhesive type	pressure-sensitive
	Adhesive appearance	clear
	Adhesion	1.75 to 3.5 [N/25mm]

Each tape has a different adhesion, designed to work with the films, inks and graphic protection as recommended in this bulletin.

Application method dry only!

Usage Recommendations Application tape is not required for all films or types of application. It is even specifically not recommended for certain film or application. The type of premasking or prespacing tape to use depends on the type of graphics produced and the last component (ink, overlaminated or clear) that was applied to the graphic construction.

When to use an Application Tape An application tape can reduce stretching, wrinkling and air entrapment during hand application of the graphic. Typically we recommend the usage of an application tape when the graphic meets at least one of these criteria:

- graphic construction is less than 100 µm
- striping or intricately-cut graphics
- cut graphics; eliminates the time consuming layout of individual parts on the application surface.

Important!

Always check for ease of part pick up before releasing the job. This is particularly important if the cut graphics include small letters, narrow stroke letters or intricate designs.
Graphic film with Controltac™ and/or Comply™ should not be removed from the liner and then be reapplied to the liner. These key application features will be lost if you prematurely remove the liner.

Do not use an application tape for graphic installations on textured substrates. The graphic may not have enough initial adhesion to the substrate to allow tape removal without lifting the film of the substrate.

Surface	Large format (> 0.5 m ²)	Small format (< 0.5 m ²)
Most unprinted Scotchcal™, Controltac™ films	SCPM-19	SCPS-100
Graphics with exposed Comply™ liner	SCPS-55	
Premium ElectroCut™ films (SC100, SC220)	SCPS-100	SCPS-2
Scotchprint® Wrap Film 1080	SCPS-55	
Glass decoration films SC7725SE	SCPS-55	
Mirror films SC7755SE	SCPS-2	
Intermediate and promotional ElectroCut™ films SC30, SC50, SC2330, SC5525SE	IAT ecg	
Most overlaminates	SCPM-19	SCPS-100
Thick overlaminates (i.e. graphics for floors)	not required	
Overlaminates for window graphics SC8914i	not recommended	
Solvent inks, uncleared	SCPS-100	
Most solvent clears	SCPS-100	
8920	SCPM-44X	
1955abc	SCPS-100	SCPS-2
Film 3545C with solvent clear	SCPM-44X	Do not use this products for prespaced graphics
UV inks, uncleared	SCPM-44X	
Most UV clears	SCPM-44X	

Shelf Life, Storage and Handling

Storage conditions!	Tape ages especially when stored at elevated temperatures. Its adhesive becomes more aggressive. Unrolling the tape during mechanical application can cause the tape to stretch resulting in pop-off and curl of the graphic. If graphic film applied with tape has been improperly stored, the removal of the tape after graphic installation might be more difficult and result in edge lifting.
Unused application tape	Shelf life is 1 year from the date of purchase in a cool, dry place out of sunlight.
Graphics with application tape applied	After the tape has been applied store the graphic in a cool, dry place out of sunlight. Store flat or wrapped onto a core with a minimum diameter of 150 mm (6"). Very stiff films (i.e. reflective material) store flat only. Apply the finished graphic within one year from the date of its processing.

Remarks

This bulletin provides technical information only.

Important Notice

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Additional Information

Visit the web site of your local subsidiary at www.3mgraphics.com for getting more:

- details about 3M MCS Warranty and 3M Performance Guarantee
- additional instruction bulletins
- a complete product overview about materials 3M is offering.

3M Europe S.A./N.V.

Hermeslaan 7;
1831 Diegem, Belgium

Responsible for this technical product bulletin

3M Deutschland GmbH | Display & Graphics Laboratory
Carl-Schurz-Str. 1 | 41453 Neuss, Germany

*3M, Controltac, Scotchcal, Comply and MCS are trademarks of 3M Company.
All other trademarks are the property of their respective owners.
The use of trademark signs and brand names in this bulletin is based upon
US standards. These standards may vary from country to country outside the USA.*